

# **FOAMCOAT**<sup>TM</sup>

Rosco Foamcoat<sup>™</sup> is a non-toxic, water-based coating for styrofoam and polystyrene foam, as well as other surfaces. It provides a hard, durable finish that resists chipping and cracking, yet can be sanded smooth or carved to add detailing. Foamcoat<sup>™</sup> can be used on a wide variety of surfaces including foam, primed wood, concrete block, primed fiberglass, paper maché, muslin and many other materials. Foamcoat<sup>™</sup> is fully compatible with all Rosco paints used either as tints or as surface coatings. Foamcoat<sup>™</sup> is inherently flame retardant and water resistant.



## APPLICATION

Apply by brush, roller, or Hopper spray gun depending on the desired finish. The thickness of the coating is determined by the application. When coating over fine details, use successive thin coats to build up a protective layer without obscuring the details. For an extra smooth finish without sanding, smooth the coated surface with a wet sponge just before the Foamcoat<sup>™</sup> has set completely.

### SUGGESTED USE

Excellent for use as a protective coating for all types of foam projects. Especially useful on foam scenery or props that receive physical abuse or need to last for extended tours. It can also be used as a texturing agent that is much more durable than plaster or joint compound, or for creating custom dimensional stonework.

### SURFACE PREP

Foam: All surfaces should be clean and dry before application. Wood & Plastic: Prime surface with Rosco Tough Prime before applying Foamcoat<sup>™</sup>. For particularly difficult materials, lightly sand surfaces to give it more "tooth" before applying Foamcoat<sup>™</sup>.

### SPECIFICATIONS

Mixing	Stir well and apply straight from the container.
Color	Off-white, matte finish.
Flash Point	Non-flammable.
Coverage	Varies with application. Approximately 150 sq.ft. per gallon.
Film Thickness	Varies with application. Approximately 10-50 mm.
Dry Time	Varies with thickness of coating. Approximately 2-8 hours. Allow 24 hours for full cure.
Clean-Up	Easy clean-up with soap and water.
Shelf Life	Minimum 12 months.
Packaging	One gallon cans or 3.5 gallon pails.
Part No.	150 07100 0128 - One Gallon 150 07100 0448 - 3.5 Gallon

All technical data, recommendations and service are accurate to the best of our knowledge. Rosco assumes no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part since method of application and its use is beyond our control.