

## SAFETY DATA SHEET

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

**Product Name** : FLEXCOAT  
**Product Use** : Coating - Flame retardant  
**Chemical Family** : Not available.  
**Supplier's name and address** : **Rosco Laboratories Inc.**  
 52 Harbor View Avenue  
 Stamford, CT, United States  
 06902

**24 Hr. Emergency Tel #** : (800) 424-9300 Chemtrec U.S.  
 (703) 527-3887 Chemtrec Outside U.S.

**HMIS Rating** : \* - Chronic Hazard 0 – Minimal 1 – Slight 2 – Moderate 3 – Serious 4 – Severe  
 Health: 1 Flammability: 0 Reactivity: 0

**WHMIS Classes:**



TOXIC

### SECTION 2 – HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Appearance: liquid, thixotropic. Ammonia odor. Severe eye irritant. Harmful if inhaled or swallowed.

#### \*\*\*POTENTIAL HEALTH EFFECTS\*\*\*

**Target organs** : Eyes and respiratory system  
**Routes of exposure** : *Inhalation*: YES *Skin Absorption*: NO *Skin & Eyes*: YES *Ingestion*: YES  
**Potential acute health effects** :

*Eyes*: Causes severe eye irritation. Vapors may irritate eyes. Mists may cause irritation.  
*Skin*: May cause slight irritation.  
*Inhalation*: Possible headache, nausea. May cause lung irritation. Irritation of the nose and throat.  
*Ingestion*: Abdominal pain, Nausea, Vomiting.

**Potential chronic health effects** : None known or reported by the manufacturer.  
**Medical conditions aggravated by overexposure** : Pre-existing skin and respiratory disorders.  
**Addition health hazards** : None reported by the manufacturer.  
**Potential environmental effects** : None reported by the manufacturer.



**SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredients	CAS #	% (weight)	ACGIH TLV		OSHA PEL	
			TWA	STEL	PEL	STEL
Aqueous acrylic emulsion	Mixt-ur-e	30.0 - 60.0	N/Av	N/Av	N/Av	N/Av
Ammonia	7664-41-7	0.1 - 1.0	25 ppm TWA	35 ppm STEL	50 ppm 35 mg/m3 TWA	35 ppm TWA; STEL; 27 mg/m3 STEL
Calcium carbonate	471-34-1	15.0 - 40.0	10 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica)	N/Av	N/Av	N/Av
Aluminum trihydroxide	21645-51-2	7.0 - 13.0	N/Av	N/Av	N/Av	N/Av
Titanium dioxide	13463-67-7	1.0 - 5.0	10 mg/m3 TWA	N/Av	15 mg/m3 TWA (total dust)	N/Av
Amorphous silica	7631-86-9	1.0 - 5.0	N/Av	N/Av	N/Av	N/Av
Aluminum hydroxide	21645-51-2	1.0 - 5.0	N/Av	N/Av	N/Av	N/Av

**SECTION 4 – FIRST AID MEASURES**

Inhalation : If inhaled, move to fresh air. If irritation persists, seek prompt medical attention.  
 Skin contact : Remove and wash contaminated clothing before re-use. Wash affected areas with soap and water. If irritation occurs or persists, seek medical attention.  
 Eye contact : Immediately flush eyes with running water for at least 20 minutes. If irritation persists, seek prompt medical attention.  
 Ingestion : Do not induce vomiting without medical advice. Call a physician immediately. Clean mouth with water and drink afterwards plenty of water.  
 Notes for physician : Low degree of toxicity.

**SECTION 5 – FIRE FIGHTING MEASURES**

Fire hazards/conditions of flammability : Not flammable under normal conditions of handling.  
 Flammability classification (OSHA 29 CFR 1910. 1200) : Not flammable.  
 Flash point : 96 °C  
 Flash point Method : Seta Flash CC. Auto-ignition temperature : Not available.  
 Lower flammable limit (% by vol.) : Not applicable. Upper flammable limit (% by vol.) : Not applicable  
 Suitable extinguishing media : Does not sustain combustion. Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.  
 Explosion data: Sensitivity to mechanical impact / static discharge : Not expected to be sensitive to mechanical impact or static discharge.  
 Special fire-fighting procedures/equipment



FLEXCOAT

SDS No.:7120

SDS Preparation Date: October 1, 2016

Page 3 of 6

- Hazardous combustion products : None reported by the manufacturer.
- Oxidizing properties : Oxides of carbon.
- : None known or reported by the manufacturer.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

- Personal precautions : Caution! Spilled material may be slippery. Use care to avoid falling. Wear suitable protective clothing (see Section 8).
- Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.
- Spill response/cleanup : Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).  
Water spray: Dilute with water. Flush any residue in the spill area with water. Dispose of rinse water in accordance with local and national regulations.
- Containment : Transfer liquid to containers for recovery or disposal. Dispose of in accordance with local regulations.

**SECTION 7 – HANDLING AND STORAGE**

- Safe Handling procedures : Use and store in a cool, dry, well-ventilated area. Avoid breathing vapors. Avoid contact with eyes, skin and clothing. Do not ingest. Keep containers closed when not in use.
- Storage requirements : Store in a cool, dry, well-ventilated area. Inspect periodically for damage or leaks. Do not freeze.
- Incompatible materials : Strong oxidizers (e.g. Chlorine, Peroxides, etc.).
- Special packaging materials : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

- Ventilation and engineering measures : Local exhaust is preferable. Use with adequate ventilation. Provide adequate cross air circulation. Ensure fresh air during application and drying (for example, by opening all windows and doors or using mechanical ventilation).
- Respiratory protection : None required under normal conditions.
- Skin protection : Gloves impervious to the material are recommended.
- Eye / face protection : Use safety goggles. If splashing is anticipated, splash goggles and a face shield are recommended.
- Other protective equipment : Emergency showers and eyewash facilities should be nearby.
- General hygiene considerations : Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state : Liquid. Appearance : Thixotropic
- Odor : Sweet ammonia odor. Odor threshold : Not available.
- pH : Not available.
- Boiling point : 100 °C Specific gravity : 1.43
- Melting/Freezing point : N/Av Coefficient of water/oil distribution : Not available.
- Vapor pressure (mmHg @20°C/ 68°F): Not available. Solubility in water : Appreciable. (10.0 - 99.9%)
- Vapor density (Air = 1) : Less than 1.0 (Air = 1.0) Evaporation rate (n-Butyl acetate = 1) : Not available.
- Volatile organic Compounds (VOC's) (lbs/gal: g/l) Volatiles (% by weight) : Not available.
- : 6.0 g/l
- Viscosity : Not available.



FLEXCOAT

SDS No.:7120

SDS Preparation Date: October 1, 2016

Page 4 of 6

Special Remarks On Fire Hazards : Not flammable under normal conditions of use.

### SECTION 10 – REACTIVITY AND STABILITY DATA

Stability and reactivity : Stable under normal conditions.  
 Hazardous polymerization : Will not occur.  
 Conditions to avoid : Not applicable.  
 Materials to Avoid and Incompatibility : Oxidizing agents. Incompatible materials (see Section 7).  
 Hazardous decomposition products : Carbon dioxide, carbon monoxide and other unidentified organic compounds. Acrylic monomers.

### SECTION 11 – TOXICOLOGICAL INFORMATION

Ingredients	LC <sub>50</sub> (4hr) inh, rat	LD <sub>50</sub>	
		oral	dermal
Aqueous acrylic emulsion	N/Av	N/Av	N/Av
Ammonia	N/Av	N/Av	N/Av
Calcium carbonate	N/Av	6450 mg/kg (rat)	N/Av
Aluminum trihydroxide	N/Av	>5000 mg/kg (rat)	N/Av
Titanium dioxide	N/Av	>10000 mg/kg (rat)	N/Av
Amorphous silica	N/Av	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Aluminum hydroxide	N/Av	> 5000 mg/kg (rat)	N/Av

Toxicological data : Low order of toxicity for normal industrial handling.  
 Carcinogenic status : Contains the following chemical(s) listed as carcinogenic or possibly carcinogenic by IARC: titanium dioxide.  
 Reproductive effects : Not expected to have other reproductive effects.  
 Teratogenicity : Contains substances that may damage genetic material or cause embryotoxic/ fetotoxic effects. This product contains: Aluminum trihydroxide, Aluminum hydroxide.  
 Mutagenicity : Not expected to be mutagenic in humans.  
 Reproductive effects : Not expected to have other reproductive effects.  
 Irritancy : Irritating to eyes, respiratory system and skin.  
 Sensitization to material : Not expected to be a sensitizer.  
 Synergistic materials : None reported by the manufacturer.

### SECTION 12 – ECOLOGICAL INFORMATION

Environmental effects : None known or reported by the manufacturer. However, it is recommended not to allow the material to enter the environment.  
 Important environmental characteristics : None known or reported by the manufacturer.  
 Ecotoxicological : No data is available on the product itself.

### SECTION 13 – DISPOSAL CONSIDERATIONS

Handling for Disposal : See Section 7 (Handling and Storage) section for further details.  
 Methods of Disposal : Dispose in accordance with all applicable federal, state, provincial and local regulations. Contact your local, state, provincial or federal environmental agency for specific rules.

**SECTION 14 – TRANSPORTATION INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	Not regulated	-None-	
TDG Additional information	None.				
49CFR/DOT	None	Not regulated.	Not regulated	-None-	
49CFR/DOT Additional information	None.				
ICAO/IATA	None	Not regulated.	Not regulated	-None-	
ICAO/IATA Additional information	None.				
IMDG	None	Not regulated.	Not regulated	-None-	
IMDG Additional information	None.				

**SECTION 15 – REGULATORY INFORMATION**

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: This product contains a chemical known to the State of California to cause developmental harm. This product contains: Titanium Dioxide.

Canadian Regulations:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian WHMIS Classification: Class D2B (Materials Causing Other Toxic Effects, Toxic Material)

This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.



FLEXCOAT

SDS No.:7120

SDS Preparation Date: October 1, 2016

Page 6 of 6

**SECTION 16 – OTHER INFORMATION**

Legend : ACGIH: American Conference of Governmental Industrial Hygienists  
IARC: International Agency for Research on Cancer  
N/Ap: not applicable  
N/Av: not available  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
OSHA: Occupational Safety and Health Administration

References : Information obtained from sources including original supplier's Safety Data Sheet, and reference including RTECS and CCOHS Cheminfo.

<p><u>Prepared for:</u> Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT, USA, 06902 Phone: (203) 708 8900  <a href="http://http://www.rosco.com/">http://http://www.rosco.com/</a></p>	
---	--

**DISCLAIMER OF LIABILITY**

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

Preparation Date: October 1, 2016

**END OF DOCUMENT**