

Rosco SubFloor is a sprung floor system that was developed and tested by dancers to provide the perfect balance of sprung resilience and stability for all dance styles. An integral part of the Rosco SubFloor system is the one-inch thick, closed cell foam pads that are affixed at specific locations on the underside of each SubFloor panel. This, combined with the system's patented Wave Lock design, helps provide even shock absorption across the entire floor – even across the seams.



Most users will be able to install a Rosco SubFloor on their own. The 42" x 42" (1.07m x 1.07m) panels are constructed out of Medium Density Fiberboard (MDF) and use the unique Wave Lock design to easily slide together. Perimeter and Corner pieces are available to lock the entire floor together and Customizing Panels can be used to assemble a fully sprung floor from wall-to-wall. Because a Rosco SubFloor is not glued down, dance studio owners are able to easily disassemble the SubFloor and move it to their next studio or performance venue.



## KEY FEATURES

- Patented Wave Lock design provides an even sprung floor – even across the seams.
- Easy to install – no expensive floor contractors needed.
- Does not glue down – take the SubFloor with you to your next studio.

SubFloor Specifications			
Product ID#	Description	Dimensions	Weight
300080004242	SubFloor – Standard Panel**	Installed Dimensions: 42" x 42" x 2" 1.07m x 1.07m x 5.08m 2" Height:1" Panel + 1" Foam Pads  Shipping Dimensions: 46.25" x 46.25" x 1" 1.18m x 1.18m x 2.54cm	44.25 lbs. 20.07kg
300080404242	SubFloor – Customizing Panel**	46.25" x 46.25" x 1.5" 1.18m x 1.18m x 3.81cm 1.5" Height: 0.5" Panel + 1" Foam Pads	17.75 lbs. 8.05kg
300080100042	SubFloor – Short Perimeter	6.5" x 44" x 2" 16.51cm x 1.12m x 5.08cm	10.2 lbs. 4.62kg
300080100084	SubFloor – Long Perimeter	6.5" x 86" x 2" 16.51cm x 2.19m x 5.08cm	20 lbs. 9.07kg
300080150000	SubFloor – Outside Corner	6.5" x 25.375" x 27.5" x 2" 16.51cm x 0.645m x 0.698m x 5.08cm	8.0 lbs. 3.63kg
300080160000	SubFloor – Inside Corner	6.5" x 23.25" x 25.375" x 2" 16.51cm x 0.59m x 0.645m x 5.08cm	8.0 lbs. 3.63kg
300080200000	SubFloor – Transition Ramp	21" x 42" x 2" 0.54m x 1.07m x 5.08cm	14.5 lbs. 6.58kg
300080210000	SubFloor – Outside Corner Transition Ramp	21" x 46.375" x 46.375" x 2" 0.54m x 1.18m x 1.18m x 5.08cm	25 lbs. 11.34kg
300080220000	SubFloor – Inside Corner Transition Ramp	21" x 37.75" x 37.75" x 2" 0.54m x 0.96m x 0.96cm x 5.08cm	21.75 lbs. 9.87kg

\*\*Each SubFloor Standard and Customizing Panel ships with twelve 1" x 4.5" (2.54cm x 11.43cm) round foam pads. The pads ship separately and are designed to be installed onsite.