

Chroma Key Paint



Rosco Chroma Key Paints have been formulated with the assistance of video technicians throughout the country. They are manufactured to provide the high luminance values and color saturation for keying effects.



Color	Luminance	Vectorscope Phase Angle
Chroma Key Blue	52	342
Chroma Key Green	57	242

SPECIFICATIONS

Finish:	Matte	Dilution:	Use straight out of the can. If necessary, dilute with water. Diluting Chroma Key paints may make coverage less even.
Solvent:	Water	Surface Prep:	Surfaces should be clean, dry and free from dirt and grease. Prime porous surfaces, except fabrics, using Rosco Tough Prime. If painting a new plaster surface, prime wall with a commercial primer/sealer designed for raw plaster. Then use Rosco Tough Prime as a final preparation.
Binder Type:	Vinyl Acrylic	Application:	Stir contents before use. Do not shake. Check your batch numbers. Different batches of paint may vary slightly in color. Combine different batch numbers together to maintain color consistency throughout your project.
Film Thickness:	2 mil. dry film		Apply by brush, roller, or spray gun. Apply in thin, even, uniform coats, using a good quality brush or roller. Use overlapping strokes, keeping a wet edge. Change roller direction often to avoid patterns and streaking.
VOC Content:	Max. 50g/L		For repainting, it is recommended to re-prime with a white primer before painting the area with Rosco Chroma Key Paints - even if the color will remain the same. The white undertone will improve the luminance of your blue or green screen.
Coverage:	Approximately 300 sq. ft.per gallon		
Average Dry Time:	At 75°F (24°C) dries to the touch in 30 mins. Can be re-coated in 1-2 hours.		
Clean-Up:	Soap and water		
Packaging:	Quart (0.946L) 1 Gallon (3.79L) 5 Gallon (18.95L)		

PRODUCT NUMBER

150057100032	Chroma Key Blue - Quart
150057100128	Chroma Key Blue - 1 Gallon
150057100640	Chroma Key Blue - 5 Gallon
150057110032	Chroma Key Green - Quart
150057110128	Chroma Key Green - 1 Gallon
150057110640	Chroma Key Green - 5 Gallon

CAUTION: Do not apply when surface or air temperatures are below 50°F. Keep from freezing. Avoid prolonged contact with skin or breathing of spray. Do not take internally. Use adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

Important: Rosco Chroma Key Paints are manufactured in batches and different batches of paint may vary slightly in color. Touching up an area already painted can result in visible patches due to color inconsistencies from batch to batch. In almost every case, these patches will not affect the performance of the product.

All technical data, recommendations and service are accurate to the best of our knowledge. Rosco assumes no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part since method of application and its use is beyond our control, application and its use is beyond our control.